

PRODUCT ADVICE

MASONRY & PLASTER STABILISING PRIMER



All Farrow & Ball paints are eco friendly and comply with the latest environmental legislation regarding the VOC (volatile organic compounds) content of paints.

Availability: In 5 litre tins in white only. Dries clear. Available direct from Farrow & Ball, our Showrooms and selected stockists internationally.

Usage: For use on interior and exterior masonry, plaster surfaces and interior concrete floors which are porous, chalky or lightly degraded but otherwise structurally sound. Provides a well-bound and durable base.

Preparation: Ensure surfaces are sound, clean, dry and free from dirt, grease and other contamination.

Do not apply if there is a likelihood of rain or if the temperature is less than 10°C. Best applied early in the day to ensure it is fully dry before evening condensation.

Fungal or algal contaminated surfaces - should be cleaned with an appropriate treatment or a solution of diluted bleach and allowed to dry completely.

New cement rendered surfaces - all newly rendered surfaces must be permitted to **dry out completely** and are best left to weather for up to 6 months before sealing with any paint system. Farrow & Ball recommends seeking advice from a professional prior to painting.

Lime rendered surfaces - lime renders are intended to allow water vapour transmission, Farrow & Ball recommends obtaining structural advice from a professional before selecting a coating system.

Unsound surfaces - scrape back and brush clean. Any serious structural damage such as cracking or loose cement must be repaired before sealer is applied. Surfaces that are unsound may not successfully accept further paint layers; if in doubt seek professional advice.

Painting: **Do not paint in temperatures below 10°C or excessive heat above 30°C.** Stir thoroughly before use.

Once appropriate surface preparation is completed, apply with a good quality brush, working well into the surface to ensure good penetration. In cases of high porosity a second coat can be applied for best results.

Clean up: Clean brushes and rollers with warm soapy water.

Cleaning: N/A

Formulation: Based on a styrene acrylic resin, containing a wide spectrum biocide to protect surfaces against algal and fungal attack.

Storage: This product is water based and must be protected from frost and extreme temperatures. Use within 6 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this date.

Disposal: Though water based, please do not dispose of into watercourse. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the Environment Office at your local council.

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_UK

PRODUCT ADVICE

MASONRY & PLASTER STABILISING PRIMER



Health & Safety: Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of reach of children. **Safety Data Sheets are available for professional users on request.**

Environment:	Actual VOC content g/l	1.5 g/l
	VOC content w/w:	0.15%
	Classification:	Minimal
	2010 max. permitted limit grams per litre	30 g/l
	CATEGORY	g

Biocidal Products Regulation (EU) 528/2012 This product contains the following biocidal products:-1,2- bensiothiazol-3(2H)-one & 2-methylisothiazol-3(2H)-one.
These substances are used as in-can preservatives.
No nanomaterials are present.
Keep out of the reach of children.
Wear protective gloves (such as Nitrile gloves) and eye protection when using this product.
Avoid contact with skin and eyes.
In case of contact with eyes, rinse immediately with water and seek medical advice.
Do not empty waste paint into drains or rivers.
Contact the local Environmental Department for disposal instructions.
Safety Data Sheet available on request or from www.farrow-ball.com.

Coverage	Drying Time	Recoat Time	Sheen Level
Up to 100 m ² per 5 litres.	Touch dry 1 hour, hard dry 2 hours in good conditions.	2 hours	N/A

Issue 8 September 2013

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_UK